

014609 GPS Antennas - Dual Band Antennas - HGD-5 -

仕様

SPECIFICATIONS		GPS	Communication
ELECTRICAL	Frequency	1575.42 MHz (±1.023 MHz)	Cellular/GPS/GSM/GPRS/GPRS
	GAIN	4 dBi	Unity
	V.S.W.R	Less than 2.0	Less than 2.0
	Impedance	50 Ω	50 Ω
	Polarization	RHCP	Vertical
	Pattern	Hemispherical	Omi-Directional
	LNA	LNA Gain: 25dB±2dB Noise Figure: 2.0dB (Max) Band Att.: 20dB (min) @±50MHz Voltage: DC +3V ~ +5V (±10%) Current: 20mA (Max)	-
SPECIFICATIONS		GPS	Communication
MECHANICAL	Connector	SMA (Male) , Other Type Optional	
	Cable	1.5D-2V, RG-174 /Black Color(with label 'GPS')	
	Dimension	Ø 70mm	
	Height	15mm	
	Cover Material	PC	
	Mounting	Double-sided Tape Mount	
	Application	Dash Board or On Glass	
Operating Temperature	-30℃ ~ +80℃		
Storage Temperature	-40℃ ~ +90℃		

製品写真



寸法図

